



117Z4-GT

HALF-WAVE VACUUM RECTIFIER

117Z4-GT

GENERAL DATA

Electrical:


Heater, for Unipotential Cathode:

Voltage. 117 ac or dc volts
Current. 0.04 amp

Mechanical:

Mounting Position. Any
Maximum Overall Length 3"
Maximum Seated Length. 2-7/16"
Maximum Diameter 1-9/32"
Bulb T-9
Base Intermediate-Shell Octal 6-Pin
Basing Designation for BOTTOM VIEW 5AA

Pin 1—No Connection
Pin 2—Heater
Pin 3—No Connection



Pin 5—Plate
Pin 7—Heater
Pin 8—Cathode

HALF-WAVE RECTIFIER

Maximum Ratings, Design-Center Values:

PEAK INVERSE PLATE VOLTAGE 350 max. volts
PEAK PLATE CURRENT 540 max. ma
DC OUTPUT CURRENT. 90 max. ma
PEAK HEATER-CATHODE VOLTAGE:
Heater negative with respect to cathode 175 max. volts
Heater positive with respect to cathode 175 max. volts

Typical Operation with Capacitor-Input to Filter:

AC Plate-Supply Voltage (RMS). 117 volts
Filter-Input Capacitor 40 μ f
Min. Total Effective Plate-Supply Impedance* 30 ohms
DC Output Current. 90 ma

* When a filter-input capacitor larger than 40 μ f is used, it may be necessary to use more plate-supply impedance than the minimum value shown to limit the peak plate current to the rated value.

FEB. 1, 1949

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA